

FCAR

Brake Flush Machine

B-40

< Technical Parameter

- Volume: 10L
- Power: 80w
- Weight: 55KG
- Oil filling: 0.5L/min
- Voltage: DC12V Pressure:
- 0-0.4Mpa (4bar)
- Dimension: 50 × 65 × 110CM

< Features

- Adopting the latest "AC to DC" technology, the machine is more stable, safe, and efficient.
- The product is operated by dynamic compression. It takes only 2-3 minutes to replace the brake fluid completely, and the pressure can be adjusted.
- The product is equipped with two load cells for fully automatic replacement.
- Intelligent reminder, automatic air discharge, one-person operation, saving your time and labor.
- Pneumatic pumping function: can pump back 4 pumps at the same time.
- Fully controlled by the microcomputer, 10-inch touch LCD screen, with connector data query function



FCAR

Brake Flush Machine

B-50

< Technical Parameter

- Volume: 8L
- Power: 80w
- Weight: 25KG
- Oil filling: 0.5L/min
- Voltage: DC12V Pressure:
- 0-0.4Mpa (4bar)
- Dimension: 38 × 32 × 95CM

< Features

- Adopting the latest "AC to DC" technology, the machine is more stable, safe, and efficient.
- The product is operated by dynamic compression. It takes only 2-3 minutes to replace the brake fluid completely, and the pressure can be adjusted.
- Equipped with precision level sensors. Automatic alarm when the oil level below 10 %.
- Intelligent reminder, automatic air discharge, one-person operation, saving your time and labor.
- Pneumatic pumping function: can pump back 4 pumps at the same time.
- Can set the upper and lower limits of the fuel pressure to prevent damage to the vehicle oil tank caused by excessive pressure. Make oil change safer.



< Technical Parameter

- Volume: 10L
- Power: 80w
- Weight: 55KG
- Oil filling: 0.5L/min
- Voltage: DC12V Pressure:
- 0-0.4Mpa (4bar)
- Dimension: 50 × 65× 110CM

< Features

- Adopting the latest "AC to DC" technology, the machine is more stable, safe, and efficient.
- The product is operated by dynamic compression. It takes only 2-3 minutes to replace the brake fluid completely, and the pressure can be adjusted.
- The product is equipped with two load cells for fully automatic replacement.
- Intelligent reminder, automatic air discharge, one-person operation, saving your time and labor.
- Pneumatic pumping function: can pump back 4 pumps at the same time.
- Fully controlled by the microcomputer, 10-inch touch LCD screen, with connector data query function.



< Technical Parameter

- Volume: 8L
- Power: 80w
- Weight: 15KG
- Oil filling: 0.5L/min
- Voltage: AC220V/50Hz
- Pressure: 0-0.4Mpa (4bar)
- Dimension: 38 × 32× 95CM

< Features

- Adopting the latest "AC to DC" technology, the machine is more stable, safe, and efficient.
- The product is operated by dynamic compression. It takes only 2-3 minutes to replace the brake fluid completely.
- Equipped with precision level sensors. Automatic alarm when the oil level below 10 %.
- Intelligent reminder, automatic air discharge, one person operation, saving your time and labor.
- Made of stainless steel, it is sturdy and durable, simple and beautiful.



Technical Parameter

- Pneumatic
- Volume: 5L
- Weight: 40kg
- Working pressure: 0-120psi
- Dimension: 27 × 26 × 50CM
- Scope: small and medium-sized
- steam and diesel vehicles

Features

- It can achieve equal pressure and an equal amount of simultaneous filling and recycling.
- No need to discharge air, safe and environmentally friendly.
- With a full set of brake oil pot joints, a wide range of applications.

