

Tyre Equipment

C-020

- Semiautomatic tyre changer for Passenger Car, Light Truck and Motorcycle Wheels (with optional adapters).
- Longer cabinet suitable for bigger tyres.
- Standard two sets of $\Phi 70$ small cylinder.
- Swing arm is using 5mm thick square tube.

Features

Tilting column	
Swing arm column	✓
Leverless	
Pneumatic lock	
Helper arm	
Column cover	

Technical Data

- Power supply: 110V/220V/380V
- Motor rating: 0.75kw/1.1kw
- Rotation speed: 8rpm
- Rim diameter: 10" – 22"(OUT) 12"-24"(IN)
- Rim width: 3-16in
- Max wheel diameter: 1000mm
- Bead breaker force: 2500kg
- Operating pressure: 0.8-1MPa



Tyre Equipment

C-020H

- Semiautomatic tyre changer for Passenger Car, Light Truck and Motorcycle Wheels (with optional adapters).
- Powerful motor ensures best torque and speed .
- Standard two sets of $\Phi 70$ small cylinder.
- Twin cylinder redouble the clamping force.
- Swing arm is using 5mm thick square tube.

Features

Tilting column	
Swing arm column	✓
Leverless	
Pneumatic lock	
Helper arm	✓
Column cover	

Technical Data

- Power supply: 110V/220V/380V
- Motor rating: 0.75kw/1.1kw
- Rotation speed: 8rpm
- Rim diameter: 10" – 22"(OUT) 12"-24"(IN)
- Rim width: 3-16in
- Max wheel diameter: 1000mm
- Bead breaker force: 2500kg
- Operating pressure: 0.8-1MPa



Tyre Equipment

C-025A

- Automatic tyre changer for Passenger Car, Light Truck and Motorcycle Wheels (with optional adapters).
- Longer cabinet suitable for bigger tyres.
- Standard two sets of $\Phi 70$ small cylinder.
- Pneumatic powered tilting column.
- Motorcycle adapter is optional.

Features

Tilting column	✓
Swing arm column	
Leverless	
Pneumatic lock	✓
Helper arm	
Column cover	

Technical Data

- Power supply: 110V/220V/380V
- Motor rating: 0.75kw/1.1kw
- Rotation speed: 8rpm
- Rim diameter: 10" – 22"(OUT) 12"-24"(IN)
- Rim width: 3-16in
- Max wheel diameter: 1000mm
- Bead breaker force: 2500kg
- Operating pressure: 0.8-1MPa



Tyre Equipment

C-025H

- Automatic tyre changer for Passenger Car, Light Truck and Motorcycle Wheels (with optional adapters).
- Easy to operate with helper arm.
- Standard two sets of $\Phi 70$ small cylinder.
- Pneumatic powered tilting column.
- Motorcycle adapter is optional .

Features

Tilting column	✓
Swing arm column	
Leverless	
Pneumatic lock	✓
Helper arm	✓
Column cover	

Technical Data

- Power supply: 110V/220V/380V
- Motor rating: 0.75kw/1.1kw
- Rotation speed: 8rpm
- Rim diameter: 10" – 22"(OUT) 12"-24"(IN)
- Rim width: 3-16in
- Max wheel diameter: 1000mm
- Bead breaker force: 2500kg
- Operating pressure: 0.8-1MPa



Tyre Equipment

C-025AH

- Automatic tyre changer for Passenger Car, Light Truck and Motorcycle Wheels (with optional adapters)
- Longer cabinet suitable for bigger tyres
- Standard two sets of $\Phi 70$ small cylinder
- Pneumatic powered tilting column
- Motorcycle adapter is optional

Features

Tilting column	✓
Swing arm column	
Leverless	
Pneumatic lock	✓
Helper arm	✓
Column cover	✓

Technical Data

- Power supply: 110V/220V/380V
- Motor rating: 0.75kw/1.1kw
- Rotation speed: 8rpm
- Rim diameter: 10" – 22"(OUT) 12"-24"(IN)
- Rim width: 3-16in
- Max wheel diameter: 1000mm
- Bead breaker force: 2500kg
- Operating pressure: 0.8-1MPa



Tyre Equipment

C-030H

- Higher and longer right/left side helper arms system.
- Pneumatic controlled tyre pressing device can be freely lifted and located at any position.
- Multi-function helper arm has central positioning function which can make wheel and turntable homocentric.
- Tyre pressing roller of right helper arm always protects tyre and rim.
- Motorcycle adapter is optional.

Features

Tilting column	
Swing arm column	✓
Leverless	
Pneumatic lock	✓
Helper arm	✓
Column cover	

Technical Data

- Power supply: 110V/220V/380V
- Motor rating: 0.75kw/1.1kw
- Rotation speed: 8rpm
- Rim diameter: 10" – 22"(OUT) 12"-24"(IN)
- Rim width: 3-16in
- Max wheel diameter: 1000mm
- Bead breaker force: 2500kg
- Operating pressure: 0.8-1MPa



Tyre Equipment

C-035

- Automatic center postrimlock
- Built-in center clamping cylinder
- Polymer cone sleeve protects rim
- Motorcycle adapter is optional

Features

Tilting column	✓
Swing arm column	
Leverless	✓
Pneumatic lock	✓
Helper arm	✓
Column cover	✓

Technical Data

- Power supply: 110V/220V/380V
- Motor rating: 0.75kw/1.1kw
- Rotation speed: 8rpm
- Rim diameter: 10" – 26"
- Rim width: 3-16in
- Max wheel diameter: 1200mm
- Bead breaker force: 2500kg
- Operating pressure: 0.8-1MPa



Tyre Equipment

C-040

- Particularly suitable for truck tyres, farm vehicle tyres, passenger car tyres and industrial vehicle tyres with deep grooved rims, tubeless tyres with ring Built-in center clamping cylinder.
- All movements of the working parts are guided by the mobile.
- Clockwise and anticlockwise rotation of chuck.
- Universal self-centering chuck.
- Hydraulic motor with quick rotation.
- Low-voltage control handle.

Technical Data

- Hydraulic pump motor: 110V/220V/380V 50Hz/60Hz
(1PH/3PH is optional)
- Rim diameter: 14" – 26"
- Max wheel diameter: 1600mm
- Max wheel width: 780mm
- Max wheel weight: 500kg
- Hydraulic pump motor: 1.5kw 380V-3Ph (220V is optional)
- Bead breaking force: 2500kgf
- Operation control voltage: 24V



Tyre Equipment

P-040

Technical Data

- Power supply: 110V/220V/380V
50Hz/60Hz(optional)
- Motor rating: 0.25kw
- Rotation speed: 120rpm
- Rim diameter: 508mm – 610mm
- Wheel diameter: 559mm – 1050mm
- Wheel weight: 60kg



	Bracket	✓
	Measure arm	
	OPT-Program	✓
	ALU	✓
	Hide	
	SPL	
	Fn	
	Magnetic levitation	
	Screen display	

Supplied with

- Car cone set
- Wingnut & shaft
- Rim width caliper
- Hex wrench
- Pliers
- Operation guide

STANDARD ACCESSORIES							OPTIONAL		
Centering-cone	Shaft	Quick nut kit	Pliers	Hexagon key	Caliper	Protection hood	Adapter		
 Car cone set 40mm	 40mm	 40mm		 calibration weight 100g	 Wheel width caliper		 Universal Adapter	 CSTA	 18mm XLT
							 14mm MC		

Tyre Equipment

P-050

Technical Data


- Power supply: 110V/220V/380V
50Hz/60Hz(optional)
- Motor rating: 0.25kw
- Rotation speed: 120rpm
- Rim diameter: 508mm – 610mm
- Wheel diameter: 559mm – 1050mm
- Wheel weight: 60kg



	Bracket	✓
	Measure arm	
	OPT-Program	✓
	ALU	✓
	Hide	
	SPL	
	Fn	
	Magnetic levitation	
	Screen display	

Supplied with

- Car cone set
- Wingnut & shaft
- Rim width caliper
- Hex wrench
- Pliers
- Operation guide

STANDARD ACCESSORIES							OPTIONAL		
Centering-cone	Shaft	Quick nut kit	Pliers	Hexagon key	Caliper	Protection hood	Adapter		
 Car cone set 40mm	 40mm	 40mm		 calibration weight 100g	 Wheel width caliper		 Universal Adapter  CSTA	 18mm XLT	 14mm MC

Tyre Equipment

P-055

Technical Data

- Power supply: 110V/220V/380V
50Hz/60Hz(optional)
- Motor rating: 0.25kw
- Rotation speed: 120rpm
- Rim diameter: 508mm – 610mm
- Wheel diameter: 559mm – 1050mm
- Wheel weight: 70kg



	Bracket	✓
	Measure arm	✓
	OPT-Program	✓
	ALU	✓
	Hide	
	SPL	
	Fn	
	Magnetic levitation	
	Screen display	✓

Supplied with

- Car cone set
- Wingnut & shaft
- Rim width caliper
- Hex wrench
- Pliers
- Operation guide

STANDARD ACCESSORIES							OPTIONAL	
Centering-cone	Shaft	Quick nut kit	Pliers	Hexagon key	Caliper	Protection hood	Universal Adapter	CSTA
								
Car cone set				calibration weight	Wheel width caliper			
40mm	40mm	40mm		100g			18mm XLT	14mm MC

Tyre Equipment

P-045

Technical Data



- Power supply: 110V/220V/380V
50Hz/60Hz(optional)
- Motor rating: 0.25kw
- Rotation speed: 120rpm
- Rim diameter: 508mm – 610mm
- Wheel diameter: 559mm – 1050mm
- Wheel weight: 70kg



	Bracket	✓
	Measure arm	✓
	OPT-Program	✓
	ALU	✓
	Hide	
	SPL	
	Fn	
	Magnetic levitation	
	Screen display	

Supplied with

- Car cone set
- Wingnut & shaft
- Rim width caliper
- Hex wrench
- Pliers
- Operation guide

STANDARD ACCESSORIES							OPTIONAL		
Centering-cone	Shaft	Quick nut kit	Pliers	Hexagon key	Caliper	Protection hood	Universal Adapter	CSTA	
									
40mm	40mm	40mm		100g			18mm XLT	14mm MC	

Tyre Equipment

P-060

Technical Data

- Power supply: 110V/220V/380V
50Hz/60Hz(optional)
- Motor rating: 0.25kw
- Rotation speed: 120rpm
- Rim diameter: 508mm – 762mm
- Wheel diameter: 559mm – 1168mm
- Wheel weight: 80kg



	Bracket	✓
	Measure arm	✓
	OPT-Program	✓
	ALU	✓
	Hide	✓
	SPL	✓
	Fn	✓
	Magnetic levitation	✓
	Screen display	

Supplied with

- Car cone set
- Wingnut & shaft
- Rim width caliper
- Hex wrench
- Pliers
- Operation guide

STANDARD ACCESSORIES							OPTIONAL	
Centering-cone	Shaft	Quick nut kit	Pliers	Hexagon key	Caliper	Protection hood	Adapter CSTA	
								
Car cone set				calibration weight	Wheel width caliper		18mm XLT	14mm MC
40mm	40mm	40mm		100g				

Tyre Equipment

P-066

Technical Data


- Power supply: 110V/220V/380V
50Hz/60Hz(optional)
- Motor rating: 0.25kw
- Rotation speed: 120rpm
- Rim diameter: 508mm – 762mm
- Wheel diameter: 559mm – 1168mm
- Wheel weight: 80kg



	Bracket	✓
	Measure arm	✓
	OPT-Program	✓
	ALU	✓
	Hide	✓
	SPL	✓
	Fn	✓
	Magnetic levitation	✓
	Screen display	✓

Supplied with

- Car cone set
- Wingnut & shaft
- Rim width caliper
- Hex wrench
- Pliers
- Operation guide

STANDARD ACCESSORIES							OPTIONAL	
Centering-cone	Shaft	Quick nut kit	Pliers	Hexagon key	Caliper	Protection hood	Adapter	
 Car cone set 40mm	 40mm	 40mm		 calibration weight 100g	 Wheel width caliper		 Universal	 CSTA
							 18mm XLT	 14mm MC

Tyre Equipment

P-077

Technical Data


- Power supply: 110V/220V/380V
50Hz/60Hz(optional)
- Motor rating: 0.25kw
- Rotation speed: 120rpm
- Rim diameter: 508mm – 762mm
- Wheel diameter: 559mm – 1168mm
- Wheel weight: 80kg



	Bracket	✓
	Measure arm	✓
	OPT-Program	✓
	ALU	✓
	Hide	✓
	SPL	✓
	Fn	✓
	Magnetic levitation	✓
	Screen display	✓

Supplied with

- Car cone set
- Wingnut & shaft
- Rim width caliper
- Hex wrench
- Pliers
- Operation guide

STANDARD ACCESSORIES							OPTIONAL	
Centering-cone	Shaft	Quick nut kit	Pliers	Hexagon key	Caliper	Protection hood	Adapter CSTA	
								
Car cone set				calibration weight	Wheel width caliper			
40mm	40mm	40mm		100g			18mm XLT	14mm MC

Tyre Equipment

P-080

Features

- Easy operation of lifting device and mount-demount tyre with protection lever, well-consideration safety and stable.
- The microprocessor is composed of integrate circuit, with high-capacity and high-stability can realize the converting of big or small model wheels, suitable for truck, bus, car and motorcycle wheels.
- Equipped with breaking pedal.

Technical Data

- Power supply: 110V/220V/380V
- Motor power: 550W
- Rim diameter: 13"-24"
- Max wheel diameter: 1200mm
- Max wheel weight: 150kg
- Balancing precision: $\pm 10g$
- Balancing speed: 190r/min
- Noise: <70dB



Tyre Equipment

E-120

Features

- This machine is suitable for fixing and expanding tires in the repair process of various tires, making the repair work safer and faster.
- Thickened steel plate, strong and durable, long service life.

Technical Data

- | | |
|---------------------------------------|-----------|
| • Pneumatic pressure: | 8-10 bar |
| • Tire expanding range: | 65-1200mm |
| • Max spreading length of inner tire: | 300mm |
| • Net weight: | 40kg |
| • LED work light: | 24V 3W |

