

ACCESSORY

Check Valve



CV01



CV02



CV03



CV04



CV05



CV06



CV07



CV08



CV09



CV10



CV11



CV12

Item	Description	Item	Description
CV01	Male: 7/16"SAE Female: 1/2"SAE	CV07	Male: 7/16"SAE Female: 7/16"SAE
CV02	Male: 7/16"SAE Female: 1/2"SAE 45°	CV08	Male: 1/2"SAE Female: 1/2"SAE 45°
CV03	Male: 7/16"SAE Female: 1/2"SAE 60°	CV09	Male: 1/2"SAE Female: 1/2"SAE 60°
CV04	Male: 1/2"SAE Female: 1/2"SAE	CV10	Male: 1/2"SAE Female: 7/16"SAE
CV05	Male: 7/16"SAE Female: 7/16"SAE 45°	CV11	Male: 1/2"SAE Female: 7/16"SAE 45°
CV06	Male: 7/16"SAE Female: 7/16"SAE 60°	CV12	Male: 1/2"SAE Female: 7/16"SAE 60°

Adapter



V01



V02



V03



V04



V05



V06



V07



V08

Item	Description	Item	Description
V01	Male: 1/2"SAE Female: 1/2" SAE	V05	Male: 7/16"SAE Female: 1/2" SAE
V02	Male: 7/16"SAE Female: 1/2" SAE	V06	Male: 1/2"SAE Female: 7/16" SAE
V03	Male: 1/2"SAE Female: 7/16" SAE	V07	Male: 7/16"SAE Female: 1/2" SAE
V04	Male: 7/16"SAE Female: 7/16" SAE	V08	Male: 1/2"SAE Female: 7/18" SAE

LEAK DETECTOR

VLD-2

Accurate Detect

- With three different sensitiveness
- High sensitivity
- Fast response
- suit for different refrigerants



SPECIFICATIONS

Dimension	230×83×50 mm
Weight	380g
Battery	4 × 1.5V AA Battery
Battery life	8 hours
Sensitivity	10 ppm
Sensor life	1 year
Operating temperature	0–40°C
Calibration	Automatic
Response time	2 seconds
Probe length	400mm

Refrigerants

R11/R123/R404A/R414B/R600A/R12/R428A/R407A/R408A
R744/R428A/R417A/R13/R134a/R422D/R422A/1234yf
R437A/R22/R290/R407C/R728/R424A/R23/R401A/R408A
R427A/R434A/R410A/R401B/R409A/R502/R422B/R113/R402A
R32/R124/R507A/R416A/R114/R402B/R413A/R508B/R420A